



SPECIFICATIONS
 Operating Voltage: 100 VAC Max
 Current Rating: 0.5Amp Max
 Contact Resistance: 30 Milliohms Max.
 Insulation Resistance: 500 Megohms Min.
 Dielectric Withstanding Voltage: 500VAC RMS.
 Operating Temperature: -40°C To +85°C
 Accommodated FFC/FPC Thickness: 0.25~0.35mm
 Processing Temperature: 230°C~250°C For 30Second
 Base: Nylon9T; UL94V-0 Rated
 Sider: PPS; UL94V-0 Rated
 Contact: Phosphor Bronze
 Me: Phosphor Bronze
 Plating: Tin Alloy Plated

Pin	A±0.25	B±0.15	C±0.20	D±0.10	E±0.15
4	9.85	3.00	11.00	5.05	3.00
5	10.85	4.00	12.00	6.05	4.00
6	11.85	5.00	13.00	7.05	5.00
7	12.85	6.00	14.00	8.05	6.00
8	13.85	7.00	15.00	9.05	7.00
9	14.85	8.00	16.00	10.05	8.00
10	15.85	9.00	17.00	11.05	9.00
11	16.85	10.00	18.00	12.05	10.00
12	17.85	11.00	19.00	13.05	11.00
13	18.85	12.00	20.00	14.05	12.00
14	19.85	13.00	21.00	15.05	13.00
15	20.85	14.00	22.00	16.05	14.00
16	21.85	15.00	23.00	17.05	15.00
17	22.85	16.00	24.00	18.05	16.00
18	23.85	17.00	25.00	19.05	17.00
19	24.85	18.00	26.00	20.25	18.00
20	25.85	19.00	27.00	21.05	19.00
20	26.85	20.00	28.00	22.05	20.00
22	27.85	21.00	29.00	23.05	21.00
23	28.85	22.00	30.00	24.05	22.00
24	29.85	23.00	31.00	25.05	23.00
25	30.85	24.00	32.00	26.05	24.00
26	31.85	25.00	33.00	27.05	25.00
27	32.85	26.00	34.00	28.05	26.00
28	33.85	27.00	35.00	29.05	27.00
29	34.85	28.00	36.00	30.05	28.00
30	35.85	29.00	37.00	31.05	29.00
31	36.85	30.00	38.00	32.05	30.00
32	37.85	31.00	39.00	33.05	31.00
33	38.85	32.00	40.00	34.05	32.00
34	39.85	33.00	41.00	35.05	33.00

4UCON 元化興業股份有限公司
 4UCON TECHNOLOGY INC.

DRAWING No.		APPROVED BY		UNLESS OTHERWISE SPECIFIED TOLERANCES ARE .X ±0.38 .XX ±0.25 ANG.
07611		MEI		
		CHECKED BY	HZF	
		DRAWING BY	PEGA	
SCALE	NONE	REV.	A1	UNIT mm

△ A1	ADD DIM: 0.9	HZF	04/07/2008
△ A0	NEW RELEASE	HZF	05/15/2006
NO. REV.	REVISIONS	CHK	DATE